

7月コンディション



Oil Pattern Distance 44 **Reverse Brush Drop** 38 Oil Per Board 50 ul **Forward Oil Total** 12.2 mL **Reverse Oil Total** 12.6 mL **Volume Oil Total** 24.8 mL **Tank Configuration Tank A Conditioner Tank B Conditioner** A-B **ICE ICE**

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	6L	6R	1	18	29	0.0	0.0	0.0	1450
2	8L	8R	1	18	25	0.0	2.5	2.5	1250
3	9L	9R	2	18	46	2.5	7.6	5.1	2300
4	10L	10R	2	22	42	7.6	13.8	6.2	2100
5	11L	11R	2	22	38	13.8	20.0	6.2	1900
6	12L	12R	2	22	34	20.0	26.2	6.2	1700
7	13L	13R	2	22	30	26.2	32.4	6.2	1500
8	2L	2R	0	30	0	32.4	44.0	11.6	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	0	44.0	35.0	-9.0	0
2	15L	15R	2	22	22	35.0	28.8	-6.2	1100
3	13L	13R	2	22	30	28.8	22.6	-6.2	1500
4	11L	11R	2	18	38	22.6	17.5	-5.1	1900
5	9L	9R	2	18	46	17.5	12.4	-5.1	2300
6	7L	7R	2	18	54	12.4	7.3	-5.1	2700
7	5L	5R	2	14	62	7.3	3.4	-3.9	3100
8	2L	2R	0	14	0	3.4	0.0	-3.4	0

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

1200

NA NA NA Forward Reverse Combined



ltem	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	12	1.94	1.03	1.03	1.94	12

